



## Material Safety Data Sheet

Copyright, 2007, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** 3M(TM)Polystyrene Foam Insulation Spray Adhesive 78

**MANUFACTURER:** 3M

**DIVISION:** Industrial Adhesives and Tapes Division

**ADDRESS:** 3M Center  
St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

**Issue Date:** 05/18/2007

**Supersedes Date:** 10/24/2006

**Document Group:** 16-5983-8

**Product Use:**

Intended Use: aerosol adhesive  
Specific Use: aerosol insulation adhesive

### SECTION 2: INGREDIENTS

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
DIMETHYL ETHER	115-10-6	25 - 35
Nonvolatile Components N.J. Trade Secret Registry No. 04499600-6463P	Trade Secret	15 - 25
1,1-DIFLUOROETHANE	75-37-6	10 - 20
CYCLOHEXANE	110-82-7	10 - 20
Heptanes	142-82-5	3 - 7
PETROLEUM NAPHTHA	64742-48-9	1 - 5
2,3-DIMETHYLBUTANE	79-29-8	1 - 5
3-METHYLPENTANE	96-14-0	1 - 5
2-METHYLPENTANE	107-83-5	1 - 5
ACETONE	67-64-1	1 - 5
HEXANE	110-54-3	< 0.4

### SECTION 3: HAZARDS IDENTIFICATION

#### 3.1 EMERGENCY OVERVIEW

**Specific Physical Form:** Aerosol

**Odor, Color, Grade:** clear, sweet fruity odor

**General Physical Form:** Gas

**Immediate health, physical, and environmental hazards:** Closed containers exposed to heat from fire may build pressure and explode. Extremely flammable liquid and vapor. Vapors may travel long distances along the ground or floor to an ignition source and flash back. Aerosol container contains flammable material under pressure. May cause target organ effects.

### 3.2 POTENTIAL HEALTH EFFECTS

**Eye Contact:**

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

**Skin Contact:**

Delayed Dermal Irritation: Signs/symptoms may include localized redness, swelling, itching, and pain. These effects may not appear immediately following exposure.

May be absorbed through skin and cause target organ effects.

**Inhalation:**

Upper Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Intentional concentration and inhalation may be harmful or fatal.

May be absorbed following inhalation and cause target organ effects.

**Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, nausea, diarrhea and vomiting.

**Target Organ Effects:**

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Prolonged or repeated exposure, above recommended guidelines, may cause:

Liver Effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice.

Peripheral Neuropathy: Signs/symptoms may include tingling or numbness of the extremities, incoordination, weakness of the hands and feet, tremors and muscle atrophy.

Kidney Effects: Signs/symptoms may include reduced or absent urine production, increased serum creatinine, lower back pain, increased protein in urine, and increased blood urea nitrogen (BUN).

## SECTION 4: FIRST AID MEASURES

### 4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

**Eye Contact:** Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

**Skin Contact:** Wash affected area with soap and water. If signs/symptoms develop, get medical attention.

**Inhalation:** Remove person to fresh air. If signs/symptoms develop, get medical attention.

**If Swallowed:** Do not induce vomiting. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get immediate medical attention.

## SECTION 5: FIRE FIGHTING MEASURES

### 5.1 FLAMMABLE PROPERTIES

Autoignition temperature	No Data Available
Flash Point	-50 °F [Test Method: Tagliabue Closed Cup]
Flammable Limits - LEL	No Data Available
Flammable Limits - UEL	No Data Available
OSHA Flammability Classification:	Class IA Flammable Liquid

### 5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

### 5.3 PROTECTION OF FIRE FIGHTERS

**Special Fire Fighting Procedures:** Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

**Unusual Fire and Explosion Hazards:** Closed containers exposed to heat from fire may build pressure and explode. Extremely flammable liquid and vapor. Vapors may travel long distances along the ground or floor to an ignition source and flash back. Aerosol container contains flammable material under pressure.

**Note:** See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

**Accidental Release Measures:** Refer to other sections of this MSDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment. Call 3M-HELPS line (1-800-364-3577) for more information on handling and managing the spill. Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Remove all ignition sources such as flames, smoking materials, and electrical spark sources. Use only non-sparking tools. Ventilate the area with fresh air. If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available.

**In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.**

## SECTION 7: HANDLING AND STORAGE

## 7.1 HANDLING

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Keep away from heat, sparks, open flame, pilot lights and other sources of ignition. Do not pierce or burn container, even after use. No smoking while handling this material. Do not spray near flames or sources of ignition. Avoid breathing of vapors, mists or spray. Avoid eye contact with vapors, mists, or spray. Keep out of the reach of children. Vapors may ignite explosively. May cause flash fire. Prevent build-up of vapors - open all windows and doors. Maintain vapor concentrations below recommended exposure limits. Use only with cross-ventilation. Without adequate ventilation, vapors may settle in low-lying areas. Keep away from heat, sparks, and open flame. Do not smoke or ignite matches, lighters, etc.

## 7.2 STORAGE

Store away from acids. Store away from heat. Store out of direct sunlight.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1 ENGINEERING CONTROLS

Use with appropriate local exhaust ventilation. Use with functioning spray booth or local exhaust. Do not use in a confined area or areas with little or no air movement. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits and/or control mist, vapor, or spray. If ventilation is not adequate, use respiratory protection equipment. Do not use in a confined area or areas with little or no air movement. If exhaust ventilation is not adequate, use appropriate respiratory protection. Provide ventilation adequate to control vapor concentrations below recommended exposure limits and/or control spray or mist.

## 8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

### 8.2.1 Eye/Face Protection

Avoid eye contact. Avoid eye contact with vapors, mists, or spray.  
The following eye protection(s) are recommended: Safety Glasses with side shields.

### 8.2.2 Skin Protection

Avoid skin contact. Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

### 8.2.3 Respiratory Protection

Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half facepiece or fullface air-purifying respirator with organic vapor cartridges. Consult the current 3M Respiratory Selection Guide for additional information or call 1-800-243-4630 for 3M technical assistance.

### 8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

## 8.3 EXPOSURE GUIDELINES

<u><b>Ingredient</b></u>	<u><b>Authority</b></u>	<u><b>Type</b></u>	<u><b>Limit</b></u>	<u><b>Additional Information</b></u>
1,1-DIFLUOROETHANE	AIHA	TWA	1000 ppm	
1,1-DIFLUOROETHANE	CMRG	TWA	1000 ppm	
ACETONE	ACGIH	TWA	500 ppm	Table A4
ACETONE	ACGIH	STEL	750 ppm	Table A4
ACETONE	OSHA	TWA, Vacated	750 ppm	
ACETONE	OSHA	TWA	1000 ppm	Table Z-1
ACETONE	OSHA	STEL, Vacated	1000 ppm	
CYCLOHEXANE	ACGIH	TWA	100 ppm	

CYCLOHEXANE	OSHA	TWA	300 ppm	Table Z-1
DIMETHYL ETHER	AIHA	TWA	1000 ppm	
DIMETHYL ETHER	CMRG	TWA	1000 ppm	
HEXANE	ACGIH	TWA	50 ppm	Skin Notation*
HEXANE	OSHA	TWA, Vacated	50 ppm	Table Z-1A
HEXANE	OSHA	TWA	500 ppm	Table Z-1A
HEXANE (ISOMERS OTHER THAN N-HEXANE)	ACGIH	TWA	500 ppm	
HEXANE (ISOMERS OTHER THAN N-HEXANE)	ACGIH	STEL	1000 ppm	
PETROLEUM NAPHTHA	3M	TWA	100 ppm	
PETROLEUM NAPHTHA	CMRG	TWA	300 ppm	
Heptanes	CMRG	TWA	50 ppm	

\* Substance(s) refer to the potential contribution to the overall exposure by the cutaneous route including mucous membrane and eye, either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

VAC Vacated PEL: Vacated Permissible Exposure Limits [PEL] are enforced as the OSHA PEL in some states. Check with your local regulatory agency.

#### SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline

OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

**Specific Physical Form:**

Aerosol

**Odor, Color, Grade:**

clear, sweet fruity odor

**General Physical Form:**

Gas

**Autoignition temperature**

*No Data Available*

**Flash Point**

-50 °F [*Test Method:* Tagliabue Closed Cup]

**Flammable Limits - LEL**

*No Data Available*

**Flammable Limits - UEL**

*No Data Available*

**Vapor Density**

>=2.57 [*Ref Std:* AIR=1]

**Specific Gravity**

0.761 [*Ref Std:* WATER=1]

**pH**

*No Data Available*

**Melting point**

*No Data Available*

**Solubility in Water**

Nil

**Evaporation rate**

1.90 [*Ref Std:* ETHER=1]

**Hazardous Air Pollutants**

<=0.4 % weight

**Volatile Organic Compounds**

Approximately 55 % [*Test Method:* calculated SCAQMD rule 443.1]

**Percent volatile**

Approximately 80 % weight

**Viscosity**

*Not Applicable*

## SECTION 10: STABILITY AND REACTIVITY

**Stability:** Stable.

**Materials and Conditions to Avoid:** Heat

**Hazardous Polymerization:** Hazardous polymerization will not occur.

### Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Aldehydes	During Combustion
Hydrocarbons	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion

## SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

## SECTION 12: ECOLOGICAL INFORMATION

### ECOTOXICOLOGICAL INFORMATION

Not determined.

### CHEMICAL FATE INFORMATION

Not determined.

## SECTION 13: DISPOSAL CONSIDERATIONS

**Waste Disposal Method:** Incinerate in a permitted hazardous waste incinerator. As a disposal alternative, dispose of waste product in a permitted hazardous waste facility.

Facility must be capable of handling aerosol cans. RECYCLE EMPTY AEROSOL CONTAINERS WHERE AVAILABLE.

**EPA Hazardous Waste Number (RCRA):** D001 (Ignitable)

Since regulations vary, consult applicable regulations or authorities before disposal.

## SECTION 14: TRANSPORT INFORMATION

**ID Number(s):**

62-4951-4930-4, 62-4951-4931-2, 62-4951-4935-3, 62-4951-4938-7

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

## SECTION 15: REGULATORY INFORMATION

### US FEDERAL REGULATIONS

Contact 3M for more information.

#### 311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
CYCLOHEXANE	110-82-7	10 - 20

This material contains a chemical which requires export notification under TSCA Section 12[b]:

<u>Ingredient (Category if applicable)</u>	<u>C.A.S. No</u>	<u>Regulation</u>	<u>Status</u>
HEXANE	110-54-3	Toxic Substances Control Act (TSCA) 4 Test Rule Chemicals	Applicable
CYCLOHEXANE	110-82-7	Toxic Substances Control Act (TSCA) 4 Test Rule Chemicals	Applicable
ACETONE	67-64-1	Toxic Substances Control Act (TSCA) 4 Test Rule Chemicals	Applicable

### STATE REGULATIONS

Contact 3M for more information.

### CHEMICAL INVENTORIES

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

The components of this product are listed on the Canadian Domestic Substances List.

### INTERNATIONAL REGULATIONS

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 16: OTHER INFORMATION

### NFPA Hazard Classification

Health: 2 Flammability: 4 Reactivity: 0 Special Hazards: None

Aerosol Storage Code: 3

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

### Revision Changes:

Copyright was modified.

Section 2: Ingredient table was modified.

Section 14: ID Number(s) was modified.

Section 9: Property description for optional properties was modified.

**DISCLAIMER:** The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

**3M MSDSs are available at [www.3M.com](http://www.3M.com)**